Serial No. 09/551,233
Reply to Office Action of August 13, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Claims 1 – 11 (Cancelled)

12. (Previously Presented) A method of fabricating a semiconductor device having a ferroelectric capacitor, comprising the steps of:

forming an active device element on a substrate;

forming an insulation film over said substrate to cover said active device element;

forming a lower electrode layer of said ferroelectric capacitor over said insulation film, such that said lower electrode is formed on a layer containing Ti;

forming a ferroelectric film on said lower electrode as a capacitor insulation film of said ferroelectric capacitor;

crystallizing said ferroelectric film by applying a thermal annealing process in an O₂ atmosphere under a reduced total pressure in the range between 1 Torr and 40 Torr such that peeling of the ferroelectric film is substantially reduced; and forming an upper electrode layer on said ferroelectric film.

Claims 13 – 14 (Cancelled)

15. (Currently Amended) A semiconductor device, comprising: a substrate;

an active device element formed on said substrate, said active device including a ferroelectric capacitor;

an insulation film provided over said substrate to cover said active device element;

 $\mathbf{2}$

said ferroelectric capacitor comprising:

\\CS - 80458/0011 - 70226 v1

a lower electrode containing Pt provided over said insulation film;

a PZT ferroelectric film provided on said lower electrode, said PZT ferroelectric film having a columnar microstructure extending from an interface between said lower electrode and said PZT ferroelectric film in a direction substantially perpendicular to a principal surface of said lower electrode, said PZT ferroelectric film generally having a <111> orientation extending continuously from a bottom surface of said PZT ferroelectric film to a top surface of said PZT ferroelectric film and consisting of crystal grains generally having said <111> orientation and a substantially uniform grain diameter of less than about 200nm; and

an upper electrode provided on said PZT ferroelectric film.

- 16. (Previously Presented) A semiconductor device as claimed in claim 15, wherein said crystal grains constituting said PZT ferroelectric film have an average diameter of about 150 nm.
- 17. (Original) A semiconductor device as claimed in claim 15, wherein said lower electrode comprises a Ti layer and a conductor layer provided further on said Ti layer.
- 18. (Original) A semiconductor device as claimed in claim 17, wherein said conductor layer is formed of Pt.
- 19. (Previously Presented) A semiconductor device as claimed in claim17, wherein said PZT ferroelectric film has a perovskite structure.

Claims 20 – 28 (Cancelled)

3